3M Data Sheet

Fasara™ GlassShade

SH2FGAT SH2FGVG Product

Fasara Glass Shade SH2FGAK and SH2FGVG are matte film with Japnese paper design decoration, which are designed and developped especially for the interior glazing. Fasara satisfies Shatter Resistant performance defined by JIS A 5759 (almost the same as ANSI Z97.1 Shot Bag Impact Test 100feet-lb).

Transparent polyester film with surface treated	►
for Japanese paper design	
Pressure Sensitive Adhesive	
Liner	

(Model Structure)



Structure

1.A film boks like Japanes paper design, so its apperance after application has a kind of Japane Paper Door taste texture. 2. These films can also be suitable for blding purpose just like Japanse Door and also for glazing decoration of Japanese texture

3.Fasara shows the same performance as Scotchshield SH2CL shatter resistant film in the test of Interhyper Displacement defined in JE A 5759. 4.Fasara cuts UV ray to retard sun burn of cobr or furniture.

Physical Property	Product	Cobr	Thickness (withou Liner)	Adhesion		Break Strength		Ebngation
			(microm)	(N/25mmW)	(kgf/10mmW)	(N/25mmW)	(kgf/10mmW)	(%)
	SH2FGAT	Altair	83	7.0	(?0.29)	200	(?8.2)	100
	SH2FGVG	Vega	83	7.0	(?0.29)	200	(?8.2)	100
1	Measured by the method def	ined in LIS A 5759						

red by the method defined in JIS A 5759

Optical		Shading	So lar Heat		Visible Light		UV	U value		
Property	Product	Coefficient	Reflectance	Transmittance	Absorbance	Reflectance	Transmittance	Transmittance		
			(%)	(%)	(%)	(%)	(%)	(%)	(W/?K)	(kcal/?h?)
	SH2FGAT	0.73	12	52	36	16	52	<1	5.8	(App.5.0)
	SH2FGVG	0.71	12	49	39	16	48	<1	5.8	(App.5.0)

Measured by the method defined in J IS A 5759

Specimen: Film laminated 6mm thick float glass (Face of incidence: glass surface)

Shatter Resistance Fasara applied glass satisfies the performance of shatter resistant test, Type A and Type B, defined in JIS A5759.