

## TECHNICAL DATA SHEET

## **GF 213 TRAFFIC GRAFFIC<sup>TM</sup>** 3.75 MIL EMBOSSED POLYPROPYLENE FLOOR LAMINATE CLEAR PERMANENT ADHESIVE

GF 213 is a 3.75 mil clear embossed polypropylene film designed for use as an economical protective laminate for Traffic Graffic<sup>™</sup> decals. This non-glare laminate is also an environmentally friendly alternative to vinyl films. GF 213 laminate offers a permanent acrylic pressure sensitive adhesive formulated for exceptional clarity and bond for printed graphic applications. It is intended for use as a laminating film for producing short term indoor Traffic Graffic<sup>™</sup> floor decals, table and counter top applications. GF 213 is also approved for indirect food contact. The adhesive is formulated to adhere to most common printing inks. GF 213 has been rated for slip resistance based on multiple testing methods.

PRODUCT NAME	213		
FILM			
Film Type	Clear Polypropylene		
Film Thickness ( <b>mils/µm</b> )	3.75 / <mark>95</mark> (+/- 10%)		
Film Weight (gsm)	70		
Gloss (60°)	10-30		
Opacity (%)	N/A		
Tensile Strength (psi)	MD ≥ 3000 / CD ≥ 3000		
Elongation (%)	$MD \ge 500 / CD \ge 500$		
Dimensional Stability (FTM 14)	MD $\leq$ 0.60 mm / CD $\leq$ 0.50 mm		
ADHESIVE			
Adhesive Type	Emulsion Acrylic		
Adhesive Thickness (mils/µm)	0.8-1.0 / 20-25		
Adhesive Color	Clear		
Peel Strength on Stainless Steel (Ibs/in) / (N/25mm) 15 min	2.0 / 8.8		
Peel Strength on Stainless Steel (Ibs/in) / (N/25mm) 24 hrs	3.0 / 13		
LINER			
Liner Weight (#/gsm)	53 / 86		
Liner Type	White PE-Coated 1 side Kraft		
Liner Thickness (mils/µm)	3.5 / 89		
Release Force @ 300" / min (g/2")	10-25		
PERFORMANCE GUIDANCE			
Application Temperature	≥ +40 °F		
Service Temperature	-40 °F to 200 °F		
Shelf Life	1 year		
Storage Temp / Rel. Humidity	70 °F / 50%		
Outdoor Durability	Indoor only		
CERTIFICATIONS & RATINGS			
Slip Resistance	<ul> <li>· UL 410 - Classified as Slip Resistant</li> <li>· AS HB198:2014 (AS/NZS 4586) - Dry PTV: 66, Wet PTV: 30</li> <li>· ANSI A137.1/A326.3 - Dry DCOF: 0.94, Wet DCOF 0.29</li> <li>· DIN 51130 - R9</li> </ul>		
Indirect Food Contact	· 21CFR 174 thru 182 and 21 CFR 175.105 respectively		

309 S. UNION | SPARTA, MI 49345 | P:(616) 887-7387 | T:(800) 253-3664 | F:(616) 887-0537

WWW.GENERALFORMULATIONS.COM



## TECHNICAL DATA SHEET

GF 213 - 3.75 MIL EMBOSSED POLYPROPYLENE FLOOR LAMINATE CLEAR PERMANENT ADHESIVE

PRODUCT SNAPSHOT	APPLICATIONS		INK TYPE
APPLICATION	• POP/RETAIL		O SOLVENT
<b>O WET APPLY</b>	O WALL		• ECO-SOLVENT
DRY APPLY	O WRAP		<b>O</b> LATEX
LAMINATING	O WINDOW		O UV CURABLE
O MOUNTING	FLOOR		○ SCREEN
• DIE CUTTABLE	• COUNTER		• OFFSET (UV CURABLE)
O HOT STAMP	O TRANSLUCE	ΝT	• OFFSET (CONVENTIONAL)
<b>O</b> THERMAL DIE	• GENERAL SI	G N A G E	
FLATBED CUTTABLE	<ul> <li>INDOOR (SHO</li> <li>OUTDOOR</li> </ul>	0 R T - T E R M )	
SUBSTRATES	OUTDOOK		
O OEM PAINTED METAL			
O PAINTED ALUMINUM			
O STAINLESS STEEL			
PRINTED GRAPHICS			
• ACRYLIC			
FAQS			
What types of applications is GF 213 good for?		GF 213 is intended for use in producing Traffic Graffic <sup>™</sup> floor decals as well as counter mats, mouse pads, and other graphic applications.	
Does GF 213 bond to all ink types?		The permanent adhesive is formulated to adhere to most common printing inks. Test before production.	
Can I use GF 213 with any base vinyl?		Yes, although for UL approved Traffic Graffic <sup>™</sup> floor applications you must pair GF 213 with either GF 210 (tile) or GF 212 (carpet) base vinyls.	
Where can I find more information on floor graphics?		Traffic Graffic Technical Tips	

 For Standard Terms & Conditions: www.generalformulations.com/terms-conditions
 GF 213 | SEPTEMBER 2020

 309 S. UNION | SPARTA, MI 49345 | P:(616) 887-7387 | T:(800) 253-3664 | F:(616) 887-0537

## WWW.GENERALFORMULATIONS.COM